
Name	(TWID

Homework Assignment 1

Due Date: Tuesday, Sept 26, 2017

CS425 - Database Organization Results



Instructions

- Try to answer all the questions using what you have learned in class
- When writing a query, write the query in a way that it would work over all possible database instances and not just for the given example instance!

Consider the following database schema and example instance:

Student

sid	name	\mathbf{dept}
001	Alice	CS
002	Bob	EE
003	Carol	CS
004	David	PHYS

Course

	cid	${ m title}$	dept	$\operatorname{credits}$
Ì	CS425	Databases	CS	3
	CS595	Database Security	CS	3
	EE591	Microcomputers	EE	4
	EE401	VLSI Design	$_{ m EE}$	3
	PHYS571	Radiation Physics	PHYS	3

Enroll


$\operatorname{\mathbf{cid}}$	sid	grade	${f gradepoint}$
CS425	001	A	4.0
CS595	001	В	3.0
CS595	002	A	4.0
EE401	001	A	4.0
EE401	002	В	3.0
EE401	004	A	4.0
PHYS571	002	С	2.0
PHYS571	004	A	4.0

Prereq

cid	pid
CS595	CS425
EE591	EE401

Hints:

- Attributes shown with grey background form the primary key of a relation.
- The attribute *cid* and *sid* of relation *Enroll* is a foreign key to relations *Course* and *Student*, respectively. All the attributes *cid* and *pid* (except for the one in *Course*) are a foreign key to relation *Course*.
- Attribute gradepoint is converted from the letter grade (4.0 scale).



Question 1.1.1 (6 Points)

Find the names of all the students enrolled in course 'EE401'.

Solution


 $\pi_{name}(\sigma_{cid=`EE401'}(Enroll \bowtie Student))$

Question 1.1.2 (6 Points)

Write an relational algebra expression that for each student the title of the courses he/she has received an 'A' grade in. Return this information as tuples (name, title) where title and name represent the course title and student name, respectively.

Solution

 $\pi_{name,title}(\sigma_{grade='A'}(\pi_{cid,title}(Course) \bowtie Enroll \bowtie Student))$



Find the students (sid and name) that have taken at least one of the prerequisite(s) of course 'CS595' and got an 'A' grade in this prerequisite course.

Solution

 $\pi_{sid,name}(\sigma_{Enroll.cid=`CS595' \land grade=`A'}(Enroll \bowtie_{Enroll.cid=Prereq.pid}Prereq \bowtie Student))$

Question 1.1.4 (8 Points)

Find all the 'EE' students (sid and name) that have taken all the courses offered by the 'CS' department.

$$E1 \leftarrow \pi_{sid,name,cid}(\sigma_{dept=`EE'}Enroll \bowtie Student)$$

$$E2 \leftarrow \pi_{cid}(\sigma_{dept=`CS'}(Course))$$

$$E \leftarrow E1 \div E2$$

Question 1.1.5 (8 Points)

Find the IDs of all the students (sid), whose grade in 'EE401' is lower than their grade in 'CS595'.

Solution

$$E1 \leftarrow \sigma_{cid=`EE401'}(Enroll)$$

$$E2 \leftarrow \sigma_{cid=`CS595'}(Enroll)$$

$$E \leftarrow \pi_{E1.sid}(\sigma_{(E1.sid=E2.sid)\land(E1.gradepoint$$

Question 1.1.6 (8 Points)

List all the students (sid and name) who never got a grade lower than 'B' (grade point below 3.0).

$$S' \leftarrow \pi_{sid}(Student) - \pi_{sid}(\sigma_{gradepoint < 3.0}(Enroll))$$
$$S \leftarrow \pi_{sid,name}(S' \bowtie Student)$$

Question 1.1.7 (8 Points)

List the titles of all the courses that student 'Alice' has not taken.

Solution

```
\pi_{title}(Course) - \pi_{title}(\sigma_{name='Alice'}(Student \bowtie Enroll \bowtie \pi_{cid,title}(Course)))
```

Question 1.1.8 (10 Points)

List all the students and their GPA (result schema: sid and GPA). The GPA is calculated by summing up the grade of each course multiplied the number of credits for the course and then dividing the result by the total number of credits the student has taken.

Solution

```
gp \leftarrow \pi_{Enroll.cid,sid,(gradepoint*credits) \rightarrow gp}(Enroll \bowtie Course)
totalgp \leftarrow_{sid} \mathcal{G}_{sum(gp) \rightarrow tgp}(gp)
totalcre \leftarrow_{sid} \mathcal{G}_{sum(credits) \rightarrow tcr}(Enroll \bowtie Course)
result \leftarrow \pi_{totalgp.sid,(tgp/tcr) \rightarrow GPA}(totalgp \bowtie totalcre)
```

or using one aggregation

```
gp \leftarrow \pi_{Enroll.cid,sid,(gradepoint*credits) \rightarrow gp,credits}(Enroll \bowtie Course)totalgpcre \leftarrow_{sid} \mathcal{G}_{sum(gp) \rightarrow tgp,sum(credits) \rightarrow tcr}(gp)result \leftarrow \pi_{totalgp.sid,(tgp/tcr) \rightarrow GPA}(totalgpcre)
```

Question 1.1.9 (8 Points)

List all the courses (their id) and for each course return the number of courses it has as a prerequisite.

Solution

```
course prereq \leftarrow Enroll \bowtie_{Enroll.cid=Prereq.cid} Prereq
noprereq \leftarrow \pi_{cid}(Course) - \pi_{cid}(Prereq)
numpre \leftarrow_{Enroll.cid} \mathcal{G}_{count(*)}(course prereq) \cup \pi_{cid,0}(no prereq)
```

Question 1.1.10 (8 Points)

Return the number of courses for which the average grade of all students enrolled in the course is lower than 'B' (grade point below 3.0).

$$avgG \leftarrow_{cid} \mathcal{G}_{avg(gradepoint)}(Enroll)$$
$$num \leftarrow \mathcal{G}_{count(*)}(\sigma_{avg(gradepoint) < 3.0}(avgG))$$

Question 1.1.11 (10 Points)

For every course, return the names of the highest-scoring students (result schema: course title and student name).

Solution

```
nonhigh \leftarrow \pi_{Enroll.cid,Enroll.sid}(\sigma_{(Enroll.gradepoint < x.gradepoint) \land Enroll.course = x.course}(Enroll \times \rho_x(Enroll)))
cidsid \leftarrow \pi_{Enroll.cid,Enroll.sid}(\pi_{cid,sid}(Enroll) - nonhigh)
result \leftarrow \pi_{title,name}(\pi_{cid,title}(Course) \bowtie cidsid \bowtie Student)
```

Alternatively, you can use aggregation.

```
hs \leftarrow_{cid} \mathcal{G}_{max(gradepoint) \rightarrow maxgp}(Enroll)

result \leftarrow \pi_{hs.cid,name,title}(hs \bowtie_{hs.cid=Enroll.cid \land maxgp=gradepoint} Enroll \bowtie Student \bowtie \pi_{cid,title}(Course))
```

Question 1.1.12 (12 Points)

List all the students (sid and name) that are enrolled in courses for which they have taken the prerequisites.

```
cidpre \leftarrow \pi_{Enroll.cid,Enroll.sid,Prereq.pid}(Enroll \bowtie_{Enroll.cid=Prereq.cid} Prereq)
nopre \leftarrow \pi_{sid}((\pi_{cid}(Course) - \pi_{cid}(Prereq)) \bowtie Enroll)
pretaken \leftarrow \pi_{cidpre.sid}(\sigma_{(cidpre.pid=x.cid) \land (cidpre.sid=x.sid)}(cidpre \times \rho_x(Enroll)))
result \leftarrow \pi_{sid,name}((pretaken \cup nopre) \bowtie Student)
```

Question 1.1.13 (BONUS QUESTION) (10 Points)

Write a query that returns the names of all students that are ready to graduate. A student is ready to graduate if the student fulfills **all** the following requirements:

- 1. The student has a GPA of 3.0 or higher
- 2. The student has taken at least 30 credits of coursework
- 3. The student is not missing any prerequisite of the courses he/she has taken. That is, for every course the student has taken that has a prerequisite, the student has taken one or more of these prerequisites

```
gp \leftarrow \pi_{Enroll.cid,sid,(gradepoint*credits)} \rightarrow gp(Enroll \bowtie Course)
totalgp \leftarrow_{sid} \mathcal{G}_{sum(gp)\rightarrow tgp}(gp)
totalcre \leftarrow_{sid} \mathcal{G}_{sum(credits)\rightarrow tcr}(Enroll \bowtie Course)
highGPA \leftarrow \pi_{sid}(\sigma_{GPA>3.0}(\pi_{sid,(tgp/tcr)\rightarrow GPA}(totalgp \bowtie totalcre))
enoughCred \leftarrow \pi_{sid}(\sigma_{tcr\geq 30}(totalcre))
takenPreq \leftarrow \pi_{sid,cid}(Enroll \bowtie Prereq \bowtie_{pid=cid'\land sid=sid'} \pi_{cid\rightarrow cid'\land sid\rightarrow sid'}(Enroll))
hasPreq \leftarrow \pi_{sid,cid}(Enroll \bowtie Prereq)
missingPreq \leftarrow \pi_{sid}(hasPreq - takenPreq)
allPreq \leftarrow \pi_{sid}(student) - missingPreq
allReqs \leftarrow highGPA \cap enoughCred \cap allPreq
result \leftarrow \pi_{name}(students \bowtie allReqs)
```