



CS 525: Advanced Database Organization

12: Transaction Management




Boris Glavic

Slides: adapted from a [course](#) taught by [Hector Garcia-Molina](#), Stanford InfoLab

CS 525  Notes 12 - Transaction Management 1 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY


Concurrency and Recovery

- DBMS should enable multiple clients to access the database concurrently
 - This can lead to problems with correctness of data because of interleaving of operations from different clients
 - ->System should ensure correctness (**concurrency control**)

CS 525  Notes 12 - Transaction Management 2 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Concurrency and Recovery

- DBMS should enable reestablish correctness of data in the presence of failures
 - ->System should restore a correct state after failure (**recovery**)


CS 525  Notes 12 - Transaction Management 3 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Integrity or correctness of data

- Would like data to be “accurate” or “correct” at all times


EMP

Name	Age
White	52
Green	3421
Gray	1

CS 525  Notes 12 - Transaction Management 4 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY


Integrity or consistency constraints

- Predicates data must satisfy
- Examples:
 - x is key of relation R
 - $x \rightarrow y$ holds in R
 - $\text{Domain}(x) = \{\text{Red, Blue, Green}\}$
 - α is valid index for attribute x of R
 - no employee should make more than twice the average salary

CS 525  Notes 12 - Transaction Management 5 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Definition:


- Consistent state: satisfies all constraints
- Consistent DB: DB in consistent state

CS 525  Notes 12 - Transaction Management 6 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Constraints (as we use here) may not capture “full correctness”

Example 1 Transaction constraints


- When salary is updated,
new salary > old salary
- When account record is deleted,
balance = 0

CS 525  Notes 12 - Transaction Management 7 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Note: could be “emulated” by simple constraints, e.g.,


account


Acct #	...	balance	deleted?
--------	-----	---------	----------

CS 525  Notes 12 - Transaction Management 8 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Constraints (as we use here) may not capture “full correctness”

Example 2 Database should reflect real world




CS 525  Notes 12 - Transaction Management 9 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

☞ in any case, continue with constraints...

Observation: DB cannot be consistent always!

Example: $a_1 + a_2 + \dots + a_n = \text{TOT}$ (constraint)


Deposit \$100 in a_2 : $\begin{cases} a_2 \leftarrow a_2 + 100 \\ \text{TOT} \leftarrow \text{TOT} + 100 \end{cases}$

CS 525  Notes 12 - Transaction Management 10 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Example: $a_1 + a_2 + \dots + a_n = \text{TOT}$ (constraint)


Deposit \$100 in a_2 : $\begin{cases} a_2 \leftarrow a_2 + 100 \\ \text{TOT} \leftarrow \text{TOT} + 100 \end{cases}$

	:	:	:
a_2	50	150	150
	:	:	:
TOT	1000	1000	1100


CS 525  Notes 12 - Transaction Management 11 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Transactions

- **Transaction:** Sequence of operations executed by one concurrent client that preserve consistency

CS 525  Notes 12 - Transaction Management 12 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Transaction: collection of actions that preserve consistency



CS 525



Notes 12 - Transaction Management

13

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Big assumption:

If T starts with consistent state +
T executes in isolation
⇒ T leaves consistent state

CS 525



Notes 12 - Transaction Management

14

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Correctness (informally)

- If we stop running transactions, DB left consistent
- Each transaction sees a consistent DB

CS 525



Notes 12 - Transaction Management

15

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Transactions - ACID

- **A**tomicity
 - Either all or no commands of transaction are executed
- **C**onsistency
 - After transaction DB is consistent
- **I**solation
 - Transactions are running isolated from each other
- **D**urability
 - Modification executed by transaction are never lost

CS 525



Notes 12 - Transaction Management

16

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

How can constraints be violated?

- Transaction bug
- DBMS bug
- Hardware failure
 - e.g., disk crash alters balance of account
- Data sharing
 - e.g.: T1: give 10% raise to programmers
 - T2: change programmers ⇒ systems analysts

CS 525



Notes 12 - Transaction Management

17

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

How can we prevent/fix violations?

- Part 13 (Recovery):
 - due to failures
- Part 14 (Concurrency Control):
 - due to data sharing

CS 525



Notes 12 - Transaction Management

18

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Will not consider:

- How to write correct transactions
- How to write correct DBMS
- Constraint checking & repair

That is, solutions studied here do not need to know constraints

CS 525



Notes 12 - Transaction Management

19

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Operations:

- Input (x): block containing x → memory
- Output (x): block containing x → disk

CS 525



Notes 12 - Transaction Management

20

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Operations:

- Input (x): block containing x → memory
- Output (x): block containing x → disk

- Read (x,t): do input(x) if necessary
t ← value of x in block
- Write (x,t): do input(x) if necessary
value of x in block ← t

CS 525



Notes 12 - Transaction Management

21

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Key problem Unfinished transaction **(Atomicity)**

Example

Constraint: A=B

T1: A ← A × 2

B ← B × 2

CS 525




Notes 12 - Transaction Management


22

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

T1: Read (A,t); t ← t×2
Write (A,t);
Read (B,t); t ← t×2
Write (B,t);
Output (A);
Output (B);



memory



disk

CS 525




Notes 12 - Transaction Management


23

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

T1: Read (A,t); t ← t×2
Write (A,t);
Read (B,t); t ← t×2
Write (B,t);
Output (A);
Output (B);



memory



disk

CS 525



Notes 12 - Transaction Management

24

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

T1: Read (A,t); t ← tx2
 Write (A,t);
 Read (B,t); t ← tx2
 Write (B,t);
 Output (A);
 Output (B); failure!

A: ~~8~~ 16
 B: ~~8~~ 16

A: ~~8~~ 16
 B: 8

memory disk

CS 525 Notes 12 - Transaction Management 25 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Transactions in SQL

- BEGIN TRANSACTION
 - Start new transaction
- COMMIT
 - Finish and make all modifications of transactions persistent
- ABORT/ROLLBACK
 - Finish and undo all changes of transaction

CS 525 Notes 12 - Transaction Management 26 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Example

time ↓

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal + 40
 WHERE acc = 10;

 UPDATE accounts
 SET bal = bal - 40
 WHERE acc = 9;
 COMMIT;

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal * 1.05;
 COMMIT;

CS 525 Notes 12 - Transaction Management 27 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Example

time ↓

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal + 40
 WHERE acc = 10;

 UPDATE accounts
 SET bal = bal - 40
 WHERE acc = 9;
 COMMIT;

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal * 1.05;
 COMMIT;

Bank customer transfers money from account 9 to account 10

CS 525 Notes 12 - Transaction Management 28 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Example

time ↓

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal + 40
 WHERE acc = 10;

 UPDATE accounts
 SET bal = bal - 40
 WHERE acc = 9;
 COMMIT;

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal * 1.05;
 COMMIT;

Bank adds interest to all accounts

CS 525 Notes 12 - Transaction Management 29 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Example

time ↓

BEGIN TRANSACTION;
 UPDATE accounts
 SET bal = bal
 WHERE acc = 10

 UPDATE accounts
 SET bal = bal - 40
 WHERE acc = 9;
 COMMIT;

SET bal = bal * 1.05;
 COMMIT;

Potential Problems:
 1. Transactions are interrupted

- No reduction in bal of acc 9
- Only some accounts got interest

 2. Interleaving of Transaction

- Acc 9 too much interest (before 40 has been deducted)

CS 525 Notes 12 - Transaction Management 30 IIT College of Science and Letters ILLINOIS INSTITUTE OF TECHNOLOGY

Modeling Transactions and their Interleaving

- Transaction is sequence of operations
 - **read**: $r_i(x)$ = transaction i read item x
 - **write**: $w_i(x)$ = transaction i wrote item x
 - **commit**: c_i = transaction i committed
 - **abort**: a_i = transaction i aborted

CS 525



Notes 12 - Transaction Management

31

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

$$T_1 = r_1(a_{10}), w_1(a_{10}), r_1(a_9), w_1(a_9), c_1$$

time

```
BEGIN TRANSACTION;
UPDATE accounts
SET bal = bal + 40
WHERE acc = 10;
```

```
UPDATE accounts
SET bal = bal - 40
WHERE acc = 9;
```

```
COMMIT;
```

CS 525



Notes 12 - Transaction Management

32

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

$$T_1 = r_1(a_{10}), w_1(a_{10}), r_1(a_9), w_1(a_9), c_1$$

$$T_2 = r_2(a_1), w_2(a_1), r_2(a_2), w_2(a_2), r_2(a_9), w_2(a_9), r_2(a_{10}), w_2(a_{10}), c_1$$

```
BEGIN TRANSACTION;
UPDATE accounts
SET bal = bal + 40
WHERE acc = 10;
```

```
UPDATE accounts
SET bal = bal - 40
WHERE acc = 9;
COMMIT;
```

Assume we have accounts:
 a_1, a_2, a_9, a_{10}

```
BEGIN TRANSACTION;
UPDATE accounts
SET bal = bal * 1.05;
COMMIT;
```

CS 525



Notes 12 - Transaction Management

33

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Schedules

- A **schedule S** for a set of transactions $T = \{T_1, \dots, T_n\}$ is a partial order over operations of T so that
 - **S** contains a prefix of the operations of each T_i
 - Operations of T_i appear in the same order in **S** as in T_i
 - For any two conflicting operations they are ordered

CS 525



Notes 12 - Transaction Management

34

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

How to model execution order?

- Schedules model the order of the execution for operations of a set of transactions

CS 525



Notes 12 - Transaction Management

35

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Conflicting Operations

- Two operations are conflicting if
 - At least one of them is a write
 - Both are accessing the same data item
- Intuition
 - The order of execution for conflicting operations can influence result!

CS 525



Notes 12 - Transaction Management

36

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Conflicting Operations

- Examples
 - $w_1(X), r_2(X)$ are conflicting
 - $w_1(X), w_2(Y)$ are not conflicting
 - $r_1(X), r_2(X)$ are not conflicting
 - $w_1(X), w_1(X)$ are not conflicting

CS 525



Notes 12 - Transaction Management

37

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Complete Schedules = History

- A **schedule S** for T is complete if it contains all operations from each transaction in T
- We will call complete schedules **histories**

CS 525



Notes 12 - Transaction Management

38

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

$$T_1 = r_1(a_{10}), w_1(a_{10}), r_1(a_9), w_1(a_9), c_1$$

$$T_2 = r_2(a_1), w_2(a_1), r_2(a_2), w_2(a_2), r_2(a_9), w_2(a_9), r_2(a_{10}), w_2(a_{10}), c_1$$

Complete Schedule

$$S = r_2(a_1), r_1(a_{10}), w_2(a_1), r_2(a_2), w_1(a_{10}), w_2(a_2), r_2(a_9), w_2(a_9), r_1(a_9), w_1(a_9), c_1, r_2(a_{10}), w_2(a_{10}), c_1$$

Incomplete Schedule

$$S = r_2(a_1), r_1(a_{10}), w_2(a_1), w_1(a_{10})$$

Not a Schedule

$$S = r_2(a_1), r_1(a_{10}), c_1$$

CS 525



Notes 12 - Transaction Management

39

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

$$T_1 = r_1(a_{10}), w_1(a_{10}), r_1(a_9), w_1(a_9), c_1$$

$$T_2 = r_2(a_1), w_2(a_1), r_2(a_2), w_2(a_2), r_2(a_9), w_2(a_9), r_2(a_{10}), w_2(a_{10}), c_1$$

Conflicting operations

- Conflicting operations $w_1(a_{10})$ and $w_2(a_{10})$
- Order of these operations determines value of a_{10}
- S1 and S2 do not generate the same result

$$S_1 = \dots w_2(a_1) \dots w_1(a_{10})$$

$$S_2 = \dots w_1(a_1) \dots w_2(a_{10})$$

CS 525



Notes 12 - Transaction Management

40

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY

Why Schedules?

- Study properties of different execution orders
 - Easy/Possible to recover after failure
 - Isolation
 - -> preserve ACID properties
- Classes of schedules and protocols to guarantee that only "good" schedules are produced

CS 525



Notes 12 - Transaction Management

41

IIT College of Science and Letters
ILLINOIS INSTITUTE OF TECHNOLOGY